

RUSH SEAL



1652301PS • Clear Lens



1652302PS • Smoke Lens



1652310PS • Twilight Lens



EVA fitted positive seal for maximum protection



Accessories:
1652318 • Gasket Only



34 g

- + UPPER PROTECTION**
- + EVA 'POSITIVE SEAL' TO MAXIMIZE PROTECTION IN DUSTY ENVIRONMENTS.**
- + SINGLE PIECE, OPTICALLY CORRECT, 9 BASE AND DISTORTION FREE LENS**

+ LIGHT WEIGHT

bolle
SAFETY

RUSH SEAL

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
RUSH SEAL	 Clear	1652301PS	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1652302PS	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Twilight	1652310PS	I1	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Gasket kit with strap	1652318		AS/NZS 1337.1.2010	

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 1. Range of luminous transmittance 43 -88% (twilight).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory

MAIN MARKETS

- Manufacturing
- Medical and dental
- Petrochemical
- Food industry
- Construction
- Government
- Mining

LENSES

- 2mm polycarbonate
- 'ALS' anti-fog/anti-scratch coating on both sides of lens: Clear and Smoke
- Hard coating on Contrast lens
- 100% UV 385 – Clear
- 100% UV 400 – Smoke and Contrast

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **BOLLÉ CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non Applicable
FOAM	Yes
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s. Meets the requirements of splash approval when used with the supplied head strap correctly adjusted.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz