PRODUCT DATASHEET





Bullet Shaped Earplugs Bulk Pack (500prs)

UNCORDED DISPOSABLE



Features

- Class 5, 26dB for medium to high noise applications
- Bulk packaged dispenser refill
- Liniversal fit to suit most ear canals
- Optimal expansion rate for easy fitting
- High-visibility colour for easy wearer identification
- Suitable for high noise areas up to 110dB (A)

Standards & Certification

Force360 recognise that without product certification by a Notified Body all product performance testing, and adherence to standards claims cannot be independently verified. If they are not as claimed, serious safety implications for the wearer, and legal implications for the supplier and even the employer may arise.

Force360 source their entire range of hearing protection from a single manufacturing partner to ensure consistency and reliability of product, but most importantly Force360 have taken the further step of engaging a globally recognised Notified Body to audit and certify both the manufacturing process and the products.

All of Force360's hearing protection is certified to the latest AS/NZS hearing protection standards.

Specifications

Part No. Colour SLC₈₀

HWRX974 Hi-Vis Yellow Class 5, 26dB

Packaging



🖗 10 Packs





PRODUCT DATASHEET

Attenuation Data

MWRX974


Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean Attenuation	27.2	28.1	33.3	32.7	34.8	41.2	42.3
Standard Deviation	9.7	9.1	11.7	9.6	6.9	6.7	6.8
Mean-Minus-Standard Deviation	18.5	19.0	21.6	23.1	27.9	34.6	35.5

SLC80 (Sound Level Conversion)

A SLC80 (Sound Level Conversion) rating is engaged to convert the difference between the sound level of the environment in which the hearing protection is worn and the sound level reaching the wearer's ears. Under the standard people should not be exposed to sound above 85dB for more than an 8 hour period. A noise survey is then conducted and the table to the right can be used to select the appropriate Class of hearing protection required.


Level achieved by HWRX974 - Class 5, 26dB

Understanding Sound Levels



Class SLC₈₀ dB **Noise Survey Result** 1 10-13 Less than 90dB (A) 2 14-17 90dB to less than 95dB (A) 3 18-21 95dB to less than 100dB (A) 4 22-25 100dB to less than 105dB (A) 5 26+ 105dB to less than 110dB (A)

Work Scale (dB)



To request a sample or further technical advice please contact sales@force360.com.au © 2021 Private Brands Pty Ltd | May 2021

